

**GUARANTEED TECHNICAL PARTICULARS FOR OIL IMMERSED CIRCUIT  
BREAKER.**

<b>Sl. No.</b>	<b>Description</b>	<b>Unit</b>	<b>Value offered</b>
<b>1</b>	Rated Current	<b>Amp.</b>	
<b>2</b>	Specification Standard		<b>IS/IEC-60947-2</b>
<b>3</b>	Resistance at 30°C	<b>Ohm ml</b>	
<b>4</b>	Breaker losses	<b>Watt</b>	
<b>5</b>	Rated operational voltage	<b>Volt</b>	
<b>6</b>	Rated insulation voltage	<b>Volt</b>	
<b>7</b>	Short circuit endurance	<b>KA</b>	
<b>8</b>	Operational endurance (Min 10000)	<b>Nos.</b>	
<b>9</b>	Dielectric Strength	<b>KV</b>	
<b>10</b>	Over Load tripping		
<b>11</b>	Short circuit tripping		
<b>12</b>	Thermal tripping		
<b>13</b>	Magnetic tripping		
<b>14</b>	Tripping Mechanism		
<b>15</b>	Tripping temperature	<b>°C</b>	
<b>16</b>	Contacts		
<b>17</b>	Short Circuit tripping time	<b>Milliseconds</b>	
<b>18</b>	Magnetic tripping time	<b>Milliseconds</b>	
<b>19</b>	Load Management signal		